



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** FLUOPOX  
Fluorescent EPOXI MARKING  
PAINT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Industrial paint. For industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
STARDUSTCOLORS SAS  
ZA TESAN PLAN SUD, 30126 ST LAURENT, France  
Contact: info@stardustcolors.com  
Tel +33 466 506 166
- 1.4 Emergency telephone number:** +33 (0)1 45 42 59 59.(Only available during office hours; Monday-Friday; 08:00-18:00)

**SECTION 2: HAZARDS IDENTIFICATION \*\***

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1, H304  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Skin Irrit. 2: Skin irritation, Category 2, H315  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Skin Irrit. 2: H315 - Causes skin irritation  
STOT SE 3: H336 - May cause drowsiness or dizziness
- Precautionary statements:**  
P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P302+P352: IF ON SKIN: Wash with plenty of water  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively
- Substances that contribute to the classification**  
Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%); N-butyl acetate
- 2.3 Other hazards:**  
Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\***

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of additives and resins in solvents

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification  | Chemical name/Classification   | Concentration         |
|---|--|-----------------------|
| CAS: 1330-20-7<br>EC: 215-535-7<br>Index: 601-022-00-9<br>REACH: 01-2119488216-32-XXXX    | <b>Xylene<sup>(1)</sup></b> ATP CLP00  | <b>10 - &lt;25 %</b>  |
|   | Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning  |                       |
| CAS: 64742-95-6<br>EC: 918-668-5<br>Index: Non-applicable<br>REACH: 01-2119455851-35-XXXX | <b>Hydrocarbons, C9, aromatics (EC 200-753-7 &lt;0,1%)<sup>(1)</sup></b> Self-classified   | <b>10 - &lt;25 %</b>  |
|   | Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger |                       |
| CAS: 123-86-4<br>EC: 204-658-1<br>Index: 607-025-00-1<br>REACH: 01-2119485493-29-XXXX     | <b>N-butyl acetate<sup>(1)</sup></b> ATP CLP00   | <b>10 - &lt;25 %</b>  |
|   | Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning   |                       |
| CAS: 108-65-6<br>EC: 203-603-9<br>Index: 607-195-00-7<br>REACH: 01-2119475791-29-XXXX     | <b>2-methoxy-1-methylethyl acetate<sup>(2)</sup></b> ATP ATP01   | <b>2,5 - &lt;10 %</b> |
|   | Regulation 1272/2008 Flam. Liq. 3: H226 - Warning  |                       |
| CAS: 100-41-4<br>EC: 202-849-4<br>Index: 601-023-00-4<br>REACH: 01-2119489370-35-XXXX     | <b>Ethylbenzene<sup>(1)</sup></b> ATP ATP06  | <b>2,5 - &lt;10 %</b> |
|   | Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger                               |                       |
| CAS: 112-07-2<br>EC: 203-933-3<br>Index: 607-038-00-2<br>REACH: 01-2119475112-47-XXXX     | <b>2-butoxyethyl acetate<sup>(1)</sup></b> ATP CLP00   | <b>1 - &lt;2,5 %</b>  |
|   | Regulation 1272/2008 Acute Tox. 4: H312+H332 - Warning   |                       |

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

\*\* Changes with regards to the previous version

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 4: FIRST AID MEASURES (continued)**

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -



**FLUOPOX  
FLUORESCENT EPOXY MARKING PAINT**



**SECTION 7: HANDLING AND STORAGE (continued)**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137 / The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 40 °C
- Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (EH40/2005 Workplace exposure limits):

| Identification   |  | Environmental limits |         |                       |
|--|--|----------------------|---------|-----------------------|
| Xylene<br>CAS: 1330-20-7 EC: 215-535-7                         |  | WEL (8h)             | 50 ppm  | 220 mg/m <sup>3</sup> |
|  |  | WEL (15 min)         | 100 ppm | 441 mg/m <sup>3</sup> |
| N-butyl acetate<br>CAS: 123-86-4 EC: 204-658-1                 |  | WEL (8h)             | 150 ppm | 724 mg/m <sup>3</sup> |
|  |  | WEL (15 min)         | 200 ppm | 966 mg/m <sup>3</sup> |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6 EC: 203-603-9 |  | WEL (8h)             | 50 ppm  | 274 mg/m <sup>3</sup> |
|  |  | WEL (15 min)         | 100 ppm | 548 mg/m <sup>3</sup> |
| Ethylbenzene<br>CAS: 100-41-4 EC: 202-849-4                    |  | WEL (8h)             | 100 ppm | 441 mg/m <sup>3</sup> |
|  |  | WEL (15 min)         | 125 ppm | 552 mg/m <sup>3</sup> |
| 2-butoxyethyl acetate<br>CAS: 112-07-2 EC: 203-933-3           |  | WEL (8h)             | 20 ppm  | 133 mg/m <sup>3</sup> |
|  |  | WEL (15 min)         | 50 ppm  | 332 mg/m <sup>3</sup> |

**DNEL (Workers):**

| Identification   |            | Short exposure        |                       | Long exposure         |                       |
|--|------------|-----------------------|-----------------------|-----------------------|-----------------------|
|  |            | Systemic              | Local                 | Systemic              | Local                 |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7  | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable        |
|  | Dermal     | Non-applicable        | Non-applicable        | 180 mg/kg             | Non-applicable        |
|  | Inhalation | 289 mg/m <sup>3</sup> | 289 mg/m <sup>3</sup> | 77 mg/m <sup>3</sup>  | Non-applicable        |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable        |
|  | Dermal     | Non-applicable        | Non-applicable        | 25 mg/kg              | Non-applicable        |
|  | Inhalation | Non-applicable        | Non-applicable        | 150 mg/m <sup>3</sup> | Non-applicable        |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                                    | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable        |
|  | Dermal     | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable        |
|  | Inhalation | 960 mg/m <sup>3</sup> | 960 mg/m <sup>3</sup> | 480 mg/m <sup>3</sup> | 480 mg/m <sup>3</sup> |

- CONTINUED ON NEXT PAGE -



**FLUOPOX  
FLUORESCENT EPOXY MARKING PAINT**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Identification  |            | Short exposure        |                       | Long exposure         |                |
|---|------------|-----------------------|-----------------------|-----------------------|----------------|
|   |            | Systemic              | Local                 | Systemic              | Local          |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9 | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable |
|   | Dermal     | Non-applicable        | Non-applicable        | 153.5 mg/kg           | Non-applicable |
|   | Inhalation | Non-applicable        | Non-applicable        | 275 mg/m <sup>3</sup> | Non-applicable |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                    | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable |
|   | Dermal     | Non-applicable        | Non-applicable        | 180 mg/kg             | Non-applicable |
|   | Inhalation | Non-applicable        | 293 mg/m <sup>3</sup> | 77 mg/m <sup>3</sup>  | Non-applicable |
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3           | Oral       | Non-applicable        | Non-applicable        | Non-applicable        | Non-applicable |
|   | Dermal     | 102 mg/kg             | Non-applicable        | 102 mg/kg             | Non-applicable |
|   | Inhalation | 775 mg/m <sup>3</sup> | 333 mg/m <sup>3</sup> | 133 mg/m <sup>3</sup> | Non-applicable |

**DNEL (General population):**

| Identification   |            | Short exposure          |                         | Long exposure            |                          |
|--|------------|-------------------------|-------------------------|--------------------------|--------------------------|
|  |            | Systemic                | Local                   | Systemic                 | Local                    |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7  | Oral       | Non-applicable          | Non-applicable          | 1.6 mg/kg                | Non-applicable           |
|  | Dermal     | Non-applicable          | Non-applicable          | 108 mg/kg                | Non-applicable           |
|  | Inhalation | Non-applicable          | Non-applicable          | 14.8 mg/m <sup>3</sup>   | Non-applicable           |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | Oral       | Non-applicable          | Non-applicable          | 11 mg/kg                 | Non-applicable           |
|  | Dermal     | Non-applicable          | Non-applicable          | 11 mg/kg                 | Non-applicable           |
|  | Inhalation | Non-applicable          | Non-applicable          | 32 mg/m <sup>3</sup>     | Non-applicable           |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                                    | Oral       | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable           |
|  | Dermal     | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable           |
|  | Inhalation | 859.7 mg/m <sup>3</sup> | 859.7 mg/m <sup>3</sup> | 102.34 mg/m <sup>3</sup> | 102.34 mg/m <sup>3</sup> |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9                    | Oral       | Non-applicable          | Non-applicable          | 1.67 mg/kg               | Non-applicable           |
|  | Dermal     | Non-applicable          | Non-applicable          | 54.8 mg/kg               | Non-applicable           |
|  | Inhalation | Non-applicable          | Non-applicable          | 33 mg/m <sup>3</sup>     | Non-applicable           |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                       | Oral       | Non-applicable          | Non-applicable          | 1.6 mg/kg                | Non-applicable           |
|  | Dermal     | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable           |
|  | Inhalation | Non-applicable          | Non-applicable          | 15 mg/m <sup>3</sup>     | Non-applicable           |
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3                              | Oral       | 18 mg/kg                | Non-applicable          | 4.3 mg/kg                | Non-applicable           |
|  | Dermal     | 27 mg/kg                | Non-applicable          | 36 mg/kg                 | Non-applicable           |
|  | Inhalation | 499 mg/m <sup>3</sup>   | 166 mg/m <sup>3</sup>   | 67 mg/m <sup>3</sup>     | Non-applicable           |

**PNEC:**

| Identification  |              |                |                         |              |  |
|---|--------------|----------------|-------------------------|--------------|--|
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                         | STP          | 6.58 mg/L      | Fresh water             | 0.327 mg/L   |  |
|   | Soil         | 2.31 mg/kg     | Marine water            | 0.327 mg/L   |  |
|   | Intermittent | 0.327 mg/L     | Sediment (Fresh water)  | 12.46 mg/kg  |  |
|   | Oral         | Non-applicable | Sediment (Marine water) | 12.46 mg/kg  |  |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                 | STP          | 35.6 mg/L      | Fresh water             | 0.18 mg/L    |  |
|   | Soil         | 0.0903 mg/kg   | Marine water            | 0.018 mg/L   |  |
|   | Intermittent | 0.36 mg/L      | Sediment (Fresh water)  | 0.981 mg/kg  |  |
|   | Oral         | Non-applicable | Sediment (Marine water) | 0.0981 mg/kg |  |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9 | STP          | 100 mg/L       | Fresh water             | 0.635 mg/L   |  |
|   | Soil         | 0.29 mg/kg     | Marine water            | 0.0635 mg/L  |  |
|   | Intermittent | 6.35 mg/L      | Sediment (Fresh water)  | 3.29 mg/kg   |  |
|   | Oral         | Non-applicable | Sediment (Marine water) | 0.329 mg/kg  |  |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                    | STP          | 9.6 mg/L       | Fresh water             | 0.1 mg/L     |  |
|   | Soil         | 2.68 mg/kg     | Marine water            | 0.01 mg/L    |  |
|   | Intermittent | 0.1 mg/L       | Sediment (Fresh water)  | 13.7 mg/kg   |  |
|   | Oral         | 20 g/kg        | Sediment (Marine water) | 1.37 mg/kg   |  |

- CONTINUED ON NEXT PAGE -



**FLUOPOX  
FLUORESCENT EPOXY MARKING PAINT**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Identification  |              |            |                         |             |
|---|--------------|------------|-------------------------|-------------|
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3 | STP          | 90 mg/L    | Fresh water             | 0.304 mg/L  |
|   | Soil         | 0.68 mg/kg | Marine water            | 0.0304 mg/L |
|   | Intermittent | 0.56 mg/L  | Sediment (Fresh water)  | 2.03 mg/kg  |
|   | Oral         | 60 g/kg    | Sediment (Marine water) | 0.203 mg/kg |

**8.2 Exposure controls:**

**A.- General security and hygiene measures in the work place**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

| Pictogram                              | PPE                               | Labelling            | CEN Standard        | Remarks  |
|--|-----------------------------------|----------------------|---------------------|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours | <b>CE</b><br>CAT III | EN 405:2001+A1:2009 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

**C.- Specific protection for the hands**

| Pictogram                 | PPE                                   | Labelling          | CEN Standard | Remarks   |
|---------------------------|---------------------------------------|--------------------|--------------|---|
| Mandatory hand protection | Protective gloves against minor risks | <b>CE</b><br>CAT I |              | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374. |

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

**D.- Ocular and facial protection**

| Pictogram                 | PPE   | Labelling           | CEN Standard                    | Remarks   |
|---------------------------|---|---------------------|---------------------------------|---|
| Mandatory face protection | Panoramic glasses against splash/projections. | <b>CE</b><br>CAT II | EN 166:2001<br>EN ISO 4007:2012 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

**E.- Body protection**

| Pictogram                          | PPE   | Labelling            | CEN Standard   | Remarks                                     |
|------------------------------------|---|----------------------|--|---|
| Mandatory complete body protection | Antistatic and fireproof protective clothing                  | <b>CE</b><br>CAT III | EN 1149-1:2006<br>EN 1149-2:1997<br>EN 1149-3:2004<br>EN 168:2001<br>EN ISO 14116:2015<br>EN 1149-5:2008 | Limited protection against flames.          |
| Mandatory foot protection          | Safety footwear with antistatic and heat resistant properties | <b>CE</b><br>CAT III | EN 13287:2008<br>EN ISO 20345:2011   | Replace boots at any sign of deterioration. |

**F.- Additional emergency measures**

| Emergency measure | Standards                      | Emergency measure | Standards                     |
|-------------------|--------------------------------|-------------------|-------------------------------|
| Emergency shower  | ANSI Z358-1<br>ISO 3864-1:2002 | Eyewash stations  | DIN 12 899<br>ISO 3864-1:2002 |

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 49.3 % weight  
V.O.C. density at 20 °C: 491.49 kg/m<sup>3</sup> (491.49 g/L)  
Average carbon number: 7.67  
Average molecular weight: 115.26 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 487.17 kg/m<sup>3</sup> (487.17 g/L)  
EU limit for the product (Cat. A.F): 700 g/L (2010)  
Components: DCA7148D - 16,667 % v/v

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C: Liquid  
Appearance: Not available  
Colour: Not available  
Odour: Not available  
Odour threshold: Non-applicable \*

**Volatility:**

Boiling point at atmospheric pressure: 142 °C  
Vapour pressure at 20 °C: 797 Pa  
Vapour pressure at 50 °C: 31.06 (4.14 kPa)  
Evaporation rate at 20 °C: Non-applicable \*

**Product description:**

Density at 20 °C: 997 kg/m<sup>3</sup>  
Relative density at 20 °C: 0.997  
Dynamic viscosity at 20 °C: Non-applicable \*  
Kinematic viscosity at 20 °C: Non-applicable \*  
Kinematic viscosity at 40 °C: <20.5 cSt  
Concentration: Non-applicable \*  
pH: Non-applicable \*  
Vapour density at 20 °C: Non-applicable \*  
Partition coefficient n-octanol/water 20 °C: Non-applicable \*  
Solubility in water at 20 °C: Non-applicable \*  
Solubility properties: Non-applicable \*  
Decomposition temperature: Non-applicable \*  
Melting point/freezing point: Non-applicable \*  
Explosive properties: Non-applicable \*  
Oxidising properties: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

**Flammability:**

|                            |                  |
|----------------------------|------------------|
| Flash Point:               | 30 °C            |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature:  | 230 °C           |
| Lower flammability limit:  | Not available    |
| Upper flammability limit:  | Not available    |

**Explosive:**

|                        |                  |
|------------------------|------------------|
| Lower explosive limit: | Non-applicable * |
| Upper explosive limit: | Non-applicable * |

**9.2 Other information:**

|                           |                  |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index:         | Non-applicable * |

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight            | Humidity       |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable     | Not applicable   | Risk of combustion      | Avoid direct impact | Not applicable |

**10.5 Incompatible materials:**

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- CONTINUED ON NEXT PAGE -





**FLUOPOX  
FLUORESCENT EPOXY MARKING PAINT**



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Ethylbenzene (2B); Xylene (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
  - Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.
- H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

| Identification   | Acute toxicity  |                      | Genus  |
|--|-----------------|----------------------|--------|
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                       | LD50 oral       | 3500 mg/kg           | Rat    |
|  | LD50 dermal     | 15354 mg/kg          | Rabbit |
|  | LC50 inhalation | 17.2 mg/L (4 h)      | Rat    |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7  | LD50 oral       | 2100 mg/kg           | Rat    |
|  | LD50 dermal     | 1100 mg/kg (ATEi)    | Rat    |
|  | LC50 inhalation | 11 mg/L (4 h) (ATEi) |        |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9                    | LD50 oral       | 8532 mg/kg           | Rat    |
|  | LD50 dermal     | 5100 mg/kg           | Rat    |
|  | LC50 inhalation | 30 mg/L (4 h)        | Rat    |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | LD50 oral       | >2000 mg/kg          |        |
|  | LD50 dermal     | >2000 mg/kg          |        |
|  | LC50 inhalation | >20 mg/L (4 h)       |        |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                                    | LD50 oral       | 12789 mg/kg          | Rat    |
|  | LD50 dermal     | 14112 mg/kg          | Rabbit |
|  | LC50 inhalation | 23.4 mg/L (4 h)      | Rat    |

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

| Identification        | Acute toxicity |             | Genus  |
|-----------------------|----------------|-------------|--------|
|                       | LD50 oral      | LD50 dermal |        |
| 2-butoxyethyl acetate | 2100 mg/kg     | 1480 mg/kg  | Rat    |
| CAS: 112-07-2         |                |             | Rabbit |
| EC: 203-933-3         | 11 mg/L (4 h)  |             | Rat    |

**Acute Toxicity Estimate (ATE mix):**

| ATE mix    |                                       | Ingredient(s) of unknown toxicity |
|------------|---------------------------------------|-----------------------------------|
| Oral       | >2000 mg/kg (Calculation method)      | Non-applicable                    |
| Dermal     | 7339.2 mg/kg (Calculation method)     | 0 %                               |
| Inhalation | 63.12 mg/L (4 h) (Calculation method) | 0 %                               |

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

| Identification   | Acute toxicity          | Species                 | Genus      |
|--|-------------------------|-------------------------|------------|
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7  | LC50 13.5 mg/L (96 h)   | Oncorhynchus mykiss     | Fish       |
|  | EC50 3.4 mg/L (48 h)    | Ceriodaphnia dubia      | Crustacean |
|  | EC50 10 mg/L (72 h)     | Skeletonema costatum    | Algae      |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | LC50 1 - 10 mg/L (96 h) |                         | Fish       |
|  | EC50 1 - 10 mg/L        |                         | Crustacean |
|  | EC50 1 - 10 mg/L        |                         | Algae      |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                                    | LC50 62 mg/L (96 h)     | Leuciscus idus          | Fish       |
|  | EC50 73 mg/L (24 h)     | Daphnia magna           | Crustacean |
|  | EC50 675 mg/L (72 h)    | Scenedesmus subspicatus | Algae      |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9                    | LC50 161 mg/L (96 h)    | Pimephales promelas     | Fish       |
|  | EC50 481 mg/L (48 h)    | Daphnia sp.             | Crustacean |
|  | EC50 Non-applicable     |                         |            |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                       | LC50 42.3 mg/L (96 h)   | Pimephales promelas     | Fish       |
|  | EC50 75 mg/L (48 h)     | Daphnia magna           | Crustacean |
|  | EC50 63 mg/L (3 h)      | Chlorella vulgaris      | Algae      |
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3                              | LC50 80 mg/L (48 h)     | Leuciscus idus          | Fish       |
|  | EC50 37 mg/L (48 h)     | Daphnia magna           | Crustacean |
|  | EC50 500 mg/L (72 h)    | Scenedesmus subspicatus | Algae      |

**12.2 Persistence and degradability:**

| Identification  | Degradability  |                | Biodegradability |          |
|---|----------------|----------------|------------------|----------|
|   | BOD5           | COD            | Concentration    | Period   |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                         | Non-applicable | Non-applicable | Non-applicable   | 28 days  |
|   | Non-applicable | Non-applicable | % Biodegradable  | 88 %     |
|   | Non-applicable | 0.79           | % Biodegradable  | 84 %     |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                 | Non-applicable | Non-applicable | Non-applicable   | 5 days   |
|   | Non-applicable | Non-applicable | % Biodegradable  | 84 %     |
|   | Non-applicable | 0.79           | % Biodegradable  | 84 %     |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9 | Non-applicable | Non-applicable | Concentration    | 785 mg/L |
|   | Non-applicable | Non-applicable | Period           | 8 days   |
|   | Non-applicable | Non-applicable | % Biodegradable  | 100 %    |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                    | Non-applicable | Non-applicable | Concentration    | 100 mg/L |
|   | Non-applicable | Non-applicable | Period           | 14 days  |
|   | Non-applicable | Non-applicable | % Biodegradable  | 90 %     |
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3           | Non-applicable | Non-applicable | Concentration    | 30 mg/L  |
|   | Non-applicable | Non-applicable | Period           | 28 days  |
|   | 0.51           | 0.51           | % Biodegradable  | 77.3 %   |

**12.3 Bioaccumulative potential:**

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

| Identification  | Bioaccumulation potential |         |
|---|---------------------------|---------|
|   | BCF                       | Pow Log |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                         | 9                         | 2.77    |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                 | 4                         | 1.78    |
| 2-methoxy-1-methylethyl acetate<br>CAS: 108-65-6<br>EC: 203-603-9 | 1                         | 0.43    |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                    | 1                         | 3.15    |
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3           | 3                         | 1.51    |
|   | Potential                 | Low     |

**12.4 Mobility in soil:**

| Identification  | Absorption/desorption |                | Volatility                      |                |
|---|-----------------------|----------------|---------------------------------|----------------|
|   | Koc                   | Conclusion     | Henry                           | Moist soil     |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7               | 202                   | Moderate       | 524.86 Pa·m <sup>3</sup> /mol   | Yes            |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1       | Non-applicable        | Non-applicable | Non-applicable                  | Non-applicable |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4          | 520                   | Moderate       | 798.44 Pa·m <sup>3</sup> /mol   | Yes            |
| 2-butoxyethyl acetate<br>CAS: 112-07-2<br>EC: 203-933-3 | Non-applicable        | Non-applicable | 5.532E-1 Pa·m <sup>3</sup> /mol | No             |
|   | Surface tension       | Non-applicable | Moist soil                      | Yes            |

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

| Code      | Description   | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous                                  |

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP6 Acute Toxicity

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -



**FLUOPOX  
FLUORESCENT EPOXY MARKING PAINT**



**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2017 and RID 2017:



- |   |                |
|---|----------------|
| <b>14.1 UN number:</b>  | UN1263         |
| <b>14.2 UN proper shipping name:</b>  | PAINT          |
| <b>14.3 Transport hazard class(es):</b>   | 3              |
| Labels:   | 3              |
| <b>14.4 Packing group:</b>  | III            |
| <b>14.5 Environmental hazards:</b>  | No             |
| <b>14.6 Special precautions for user</b>  |                |
| Special regulations:  | 163, 367, 650  |
| Tunnel restriction code:  | D/E            |
| Physico-Chemical properties:  | see section 9  |
| Limited quantities:   | 5 L            |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable |

**Transport of dangerous goods by sea:**

With regard to IMDG 38-16:



- |   |                    |
|---|--------------------|
| <b>14.1 UN number:</b>  | UN1263             |
| <b>14.2 UN proper shipping name:</b>  | PAINT              |
| <b>14.3 Transport hazard class(es):</b>   | 3                  |
| Labels:   | 3                  |
| <b>14.4 Packing group:</b>  | III                |
| <b>14.5 Environmental hazards:</b>  | No                 |
| <b>14.6 Special precautions for user</b>  |                    |
| Special regulations:  | 223, 955, 163, 367 |
| EmS Codes:  | F-E, S-E           |
| Physico-Chemical properties:  | see section 9      |
| Limited quantities:   | 5 L                |
| Segregation group:  | Non-applicable     |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable     |

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2018:



- |   |                |
|---|----------------|
| <b>14.1 UN number:</b>  | UN1263         |
| <b>14.2 UN proper shipping name:</b>  | PAINT          |
| <b>14.3 Transport hazard class(es):</b>   | 3              |
| Labels:   | 3              |
| <b>14.4 Packing group:</b>  | III            |
| <b>14.5 Environmental hazards:</b>  | No             |
| <b>14.6 Special precautions for user</b>  |                |
| Physico-Chemical properties:  | see section 9  |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable |

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Ethanol.  
Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 15: REGULATORY INFORMATION (continued)**

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Non-applicable  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

| Section | Description       | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c     | FLAMMABLE LIQUIDS | 5000                    | 50000                   |

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885  
Control of Substances Hazardous to Health Regulations 2002 (as amended)  
EH40/2005 Workplace exposure limits  
The Waste Regulations 2011, 2011 No. 988

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances

Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (64742-95-6)

Substances that contribute to the classification (SECTION 2):

- Removed substances

Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (64742-95-6)

**Texts of the legislative phrases mentioned in section 2:**

- CONTINUED ON NEXT PAGE -



**FLUOPOX**  
**FLUORESCENT EPOXY MARKING PAINT**



**SECTION 16: OTHER INFORMATION (continued)**

H315: Causes skin irritation  
H336: May cause drowsiness or dizziness  
H412: Harmful to aquatic life with long lasting effects  
H304: May be fatal if swallowed and enters airways  
H226: Flammable liquid and vapour

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled  
Acute Tox. 4: H332 - Harmful if inhaled  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Skin Irrit. 2: H315 - Causes skin irritation  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure  
STOT SE 3: H335 - May cause respiratory irritation  
STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

Skin Irrit. 2: Calculation method  
STOT SE 3: Calculation method  
Aquatic Chronic 3: Calculation method  
Asp. Tox. 1: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -